

RNP RWY 20												
RMK	-	MAG VAR 2020 0.6°E					REF NAV AID :-					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	TEPTI	-	-	-	-	-	-	-	-	-	-
	-	BT404	-	-	-	-	-	-	-	-	-	-
INA TEPTI	IF	TEPTI	-	-	-	-	-	-	5000	230	-	-
	TF	IBT20	-	255	255.9	14.3	-	3000	-	190	-	1.0
INA TEPTI (via BT404)	IF	TEPTI	-	-	-	-	-	-	5000	230	-	-
	TF	BT404	-	255	255.9	9.3	-	-	4000	-	-	1.0
	TF	IBT20	-	255	255.7	5.0	-	3000	-	190	-	1.0
	IF	BT404	-	-	-	-	-	-	4000	-	-	-
INA BT404	TF	IBT20	-	255	255.7	5.0	-	3000	-	190	-	1.0
	IF	IBT20	-	-	-	-	-	3000	-	190	-	-
APCH	TF	FBT20	-	200	200.4	4.6	-	3000	3000	-	-	1.0
	TF	RW20	Yes	200	200.4	5.6	-	-	-	-	-3,00/50	0.3
	TF	BT410	Yes	200	200.3	2.1	-	-	3000	-	-	1.0
	DF	BT412	-	-	-	-	L	3000	-	185	-	1.0
	TF	VADSU	-	059	059.7	8.5	-	-	4000	220	-	1.0
	TF	TEPTI	-	018	018.7	15.9	-	5000	-	230	-	1.0
	HM	TEPTI	-	-	-	-	-	-	-	-	-	-

