

MELUN VILLAROCHE
STAR RNAV RWY ALL
 (Protégées pour / Protected for CAT A, B, C)

STAR RNAV RWY ALL											
RMK							MAG VAR 2020 1.1°E		REF NAVAID :		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
	-	ATTUC	-	-	-	-	-	-	-	-	-
ARSIL 5A											
	IF	ARSIL	-	-	-	-	-	-	5000	-	1,0
	TF	ATTUC	-	249	250,1	33,2	-	3000	5000	-	1,0
TRO 5A											
	IF	TRO	-	-	-	-	-	-	FL080	-	1,0
	TF	PM514	-	284	284,8	9,5	-	-		-	1,0
	TF	ATTUC	-	283	284,6	18,8	-	3000	5000	-	1,0
DJL 5A											
	IF	DJL	-	-	-	-	-	-	-	-	1,0
	TF	PM517	-	311	312,6	83,1	-	-	5000	-	1,0
	TF	ATTUC	-	310	311,5	15,6	-	3000	5000	-	1,0
PIBAT 5A											
	IF	PIBAT	-	-	-	-	-	-	-	-	1,0
	TF	PM526	-	336	337,4	85,6	-	-	5000	-	1,0
	TF	ATTUC	-	336	336,8	16,3	-	3000	5000	-	1,0
MOU 5A											
	IF	MOU	-	-	-	-	-	-	-	-	1,0
	TF	PM523	-	351	352,0	82,3	-	-	5000	-	1,0
	TF	ATTUC	-	351	351,8	18,5	-	3000	5000	-	1,0