

PRECODING RNP RWY 24

RNP RWY 24													
RMK	-	MAG VAR 2020 0.8°E							REF NAV AID :-				
Leg sequence		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG		-	TRACA	-	-	-	-	-	-	-	-	-	-
		IF	TRACA	-	-	-	-	-	2000	-	170	-	-
INA TRACA		TF	SUDOD	-	051	052.0	13.7	-	2000	-	170	-	1.0
		TF	DIPKA	-	317	318.3	4.0	L	2000	-	170	-	1.0
INA SUDOD		IF	SUDOD	-	-	-	-	-	-	-	170	-	-
		TF	DIPKA	-	317	318.3	4.0	-	2000	-	170	-	1.0
INA NUMLO		IF	NUMLO	-	-	-	-	-	-	-	170	-	-
		TF	DIPKA	-	150	151.2	3.0	-	2000	-	170	-	1.0
APCH		IF	DIPKA	-	-	-	-	-	2000	-	170	-	-
		TF	FAC24	-	240	241.2	3.4	-	2000	2000	-	-	1.0
		TF	RW24	Yes	240	241.1	6.1	-	-	-	-	-3.00 / 49	0.3
		TF	AC510	-	240	241.1	4.2	-	-	-	-	-	1.0
		TF	TRACA	-	141	141.4	6.1	L	2000	-	170	-	1.0

