

ALBERT BRAY

PRECODING RNP RWY 26

RNP RWY 26												
RMK	-							MAG VAR 2020 1.1°E			REF NAV/ID :	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	ABY	-	-	-	-	-	-	-	-	-	-
INA ROGEV	IF	ROGEV	-	-	-	-	-	-	-	200	-	-
	TF	OGLIB	-	174	175.3	5.8	-	3000	-	200	-	1.0
INA ABY	IF	ABY	-	-	-	-	-	-	-	200	-	-
	TF	AQ514	-	264	265.3	4.7	-	-	-	-	-	1.0
	TF	AQ516	-	352	353.3	5.2	-	-	-	-	-	1.0
	TF	ROGEV	-	082	082.6	13.0	-	-	-	200	-	1.0
	TF	OGLIB	-	174	175.3	5.8	-	3000	-	200	-	1.0
	IF	OGLIB	-	-	-	-	-	3000	-	200	-	-
APCH	TF	FAQ26	-	264	265.5	3.9	-	3000	3000	-	-	1.0
	TF	RW26	Yes	264	265.4	8.2	-	-	-	-	-3.00 / 54	0.3
	TF	AQ510	-	264	265.3	5.2	-	-	-	185	-	1.0
	TF	AQ512	-	354	355.3	5.0	-	-	-	-	-	1.0
	TF	ROGEV	-	081	082.5	17.3	-	-	-	200	-	1.0