

ALBERT BRAY

STAR RNAV RWY 08-26

(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 08											
RMK	GNSS only						MAG VAR 2020 1.1°E		REF NAVAID : -		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
ABY	-	-	-	-	-	-	-	-	-	-	-
BANTI 3R											
	IF	BANTI	-	-	-	-	-	-	-	-	-
	TF	IZUKE	-	085	086.4	28.7	-	3000	-	210	1.0
CMB 3R											
	IF	CMB	-	-	-	-	-	-	-	-	-
	TF	ROGEV	-	212	212.6	10.3	-	-	-	-	1.0
	TF	SULEX	-	211	212.5	5.9	-	-	-	-	1.0
	TF	ABY	-	251	252.4	4.7	-	3000	-	210	1.0

STAR RNAV RWY 26											
RMK	GNSS only						MAG VAR 2020 1.1°E		REF NAVAID : -		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
ABY	-	-	-	-	-	-	-	-	-	-	-
BANTI 3S											
	IF	BANTI	-	-	-	-	-	-	-	-	-
	TF	IKUZE	-	085	086.4	28.7	-	-	-	-	1.0
	TF	AQ512	-	052	053.5	9.6	-	-	-	-	1.0
	TF	ROGEV	-	081	082.5	17.3	-	3000	-	200	1.0
CMB 3S											
	IF	CMB	-	-	-	-	-	-	-	-	-
	TF	ROGEV	-	212	212.6	10.3	-	3000	-	200	1.0