

RNP RWY 11												
RMK	Fonctionnalité d'attente RNAV requise / RNAV holding functionality required.							MAG VAR 2020 0.3°E			REF NAVAID : -	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) /TCH (ft)	Navigation Accuracy (NM)
HLDG	-	VAGNA	Yes	225	225.0	4.6	L	5000	FL120	220	-	-
	-	ETPAR	Yes	165	165.0	4.6	L	5000	FL120	220	-	-
	-	LIBRU	Yes	260	260.0	4.6	L	5000	FL120	220	-	-
	-	DIRAX	Yes	325	325.0	4.2	L	5000	FL090	220	-	-
INA ETPAR	IF	ETPAR	-	-	-	-	-	-	-	220	-	-
	TF	BD111	-	186	186.4	14.9	-	3000	3000	220	-	1.0
	TF	IBD11	-	196	196.3	4.7	-	2000	2000	190	-	1.0
INA VAGNA	IF	VAGNA	-	-	-	-	-	-	-	-	-	-
	TF	BD111	-	250	250.1	25.5	-	3000	3000	220	-	1.0
	TF	IBD11	-	196	196.3	4.7	-	2000	2000	190	-	1.0
INA LIBRU	IF	LIBRU	-	-	-	-	-	-	-	-	-	-
	TF	BD113	-	277	276.9	11.7	-	4000	4000	220	-	1.0
	TF	BD111	-	276	276.7	18.8	L	3000	3000	220	-	1.0
	TF	IBD11	-	196	196.3	4.7	-	2000	2000	190	-	1.0
INA DIRAX	IF	DIRAX	-	-	-	-	-	-	-	-	-	-
	TF	BD113	-	359	359.0	21.7	-	4000	4000	220	-	1.0
	TF	BD111	-	276	276.7	18.8	L	3000	3000	220	-	1.0
	TF	IBD11	-	196	196.3	4.7	-	2000	2000	190	-	1.0
APCH	IF	IBD11	-	-	-	-	-	2000	2000	190	-	-
	TF	FBD11	-	106	106.3	4.0	-	2000	2000	-	-	1.0
	TF	RW11	Yes	106	106.3	5.0	-	-	-	-	-3.40°/49	0.3
	TF	BD110	Yes	106	106.4	2.0	-	-	3000	185	-	1.0
	DF	BD112	-	-	-	-	R	-	-	220	-	1.0
	TF	BD114	-	173	173.6	12.2	-	5000	-	-	-	1.0
	TF	DIRAX	-	071	071.0	10.7	L	-	-	220	-	1.0
	HM	DIRAX	Yes	325	325.0	4.2	L	5000	FL090	220	-	-

→