

RNP RWY 23												
RMK	Fonctionnalité d'attente RNAV requise/ RNAV holding functionality required.								MAG VAR 2020	00.3°E	REF NAV AID :	NIL
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	ETPAR	Yes	165	165.0	4.6	L	5000	FL120	220	-	-
	-	VAGNA	Yes	225	225.0	4.6	L	5000	FL120	220	-	-
	-	LIBRU	Yes	260	260.0	4.6	L	5000	FL120	220	-	-
	-	DIRAX	Yes	325	325.0	4.2	L	5000	FL090	220	-	-
INA ETPAR	IF	ETPAR	-	-	-	-	-	-	-	-	-	-
	TF	BD231	-	122	122.8	12.0	-	-	-	220	-	1.0
	TF	IBD23	-	135	135.5	8.3	-	3000	4200	210	-	1.0
INA VAGNA	IF	VAGNA	-	-	-	-	-	-	-	-	-	1.0
	TF	IBD23	-	224	224.7	9.1	-	3000	4200	210	-	1.0
INA LIBRU	IF	LIBRU	-	-	-	-	-	-	-	-	-	-
	TF	BD232	-	272	272.6	7.2	-	-	-	220	-	1.0
	TF	IDB23	-	315	315.6	7.8	-	3000	4200	210	-	1.0
INA DIRAX	IF	DIRAX	-	-	-	-	-	-	-	-	-	-
	TF	BD232	-	011	011.2	21.0	-	-	-	220	-	1.0
	TF	IDB23	-	315	315.6	7.8	-	3000	4200	210	-	1.0
APCH	IF	IBD23	-	-	-	-	-	3000	4200	210	-	-
	TF	FBD23	-	225	225.6	4.0	-	3000	3000	-	-	1.0
	TF	RW23	Yes	225	225.6	8.8	-	-	-	-	-3.00°/ 54	0.3
	TF	BD230	Yes	225	225.5	4.1	-	-	4000	210	-	1.0
	DF	ETPAR	-	-	-	-	R	-	-	220	-	1.0
	HM	ETPAR	Yes	165	165.0	4.6	L	4000	FL120	220	-	-

→