

ILS RWY 27											
RMK	REF NAVAID :-										
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 0.7°E			Navigation Accuracy (NM)
								MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	
↑ INA BE271	IF	BE271	-	-	-	-	-	2500	4400	185	-
	TF	IBE27	-	184	184.5	5.1	-	2500	2500	185	1.0
↑ INA IBE27	IF	IBE27	-	-	-	-	-	2500	2500	185	-
↑ INA BE272	IF	BE272	-	-	-	-	-	2500	4000	185	-
	TF	IBE27	-	004	004.5	5.1	-	2500	2500	185	1.0
↑ INA BE090	IF	BE090	Yes	-	-	-	-	2500	5000	210	-
	DF	BE276	-	-	-	-	-	2500	4000	185	1.0
	TF	BE272	-	094	094.5	5.0	-	2500	4000	185	1.0
	TF	IBE27	-	004	004.5	5.1	-	2500	2500	185	1.0
APCH ILS RWY 27	IF	IBE27	-	-	-	-	-	2500	2500	185	-
	See chart ILS RWY 27										
	-	BE280	Yes	-	-	-	-	-	4000	180	1.0
	DF	BE274	-	-	-	-	L	-	4000	185	1.0
	TF	BE272	-	094	094.3	12.7	-	2500	4000	185	1.0