

RNP RWY 05												
RMK								MAG VAR 2020 0,4° E			Ref NAVAID :	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG		BG430										RNAV1 / RNP APCH
	IF	BG430						2100	2100	185		RNAV1 / RNP APCH
INA BG430	TF	BG431		237	237,3	6,2						RNAV1 / RNP APCH
	TF	IBG05		139	139,5	3,2				160		RNAV1 / RNP APCH
INA BG431	IF	BG431						2100	2100	185		RNAV1 / RNP APCH
	TF	IBG05		139	139,5	3,2				160		RNAV1 / RNP APCH
INA BG432	IF	BG432						2100	2100	185		RNAV1 / RNP APCH
	TF	IBG05		319	319,6	2,7				160		RNAV1 / RNP APCH
APCH	IF	IBG05						2100	2100	160		RNAV1 / RNP APCH
	TF	FBG05		49	49,5	3,2		2100	2100			RNP APCH
	TF	RW05	Yes	49	49,6	6,2					-3,00 / 15	RNP APCH
	TF	BG433		49	49,7	4,5						RNP APCH
	TF	BG434		319	319,7	5	L			175		RNP APCH
	TF	BG430		210	210,9	8,2	L	2100	2100	185		RNP APCH