

RNP RWY 09												
RMK	MAG VAR 2020 0.1°E							REF NAVAID :-				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMW Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG		RL										
INA BH092	IF	BH092							5000	200		-
	TF	BH094		202	201.9	6.3			3000	200		1.0
	TF	IBH09		124	124.0	3.2		2000	2500	185		1.0
INA BH091	IF	BH091							5000	200		-
	TF	BH093		324	324.6	7.5			3000	200		1.0
	TF	IBH09		061	060.9	3.2		2000	2500	185		1.0
INA RL	IF	RL	YES						5000	200		-
	DF	BH091							5000	200		1.0
	TF	BH093		324	324.6	7.5			3000	200		1.0
APCH	TF	IBH09		061	060.9	3.2		2000	2500	185		1.0
	IF	IBH09						2000	2500	185		-
	TF	FBH09		092	092.3	3.2		2000	2000			1.0
	TF	RW09	YES	092	092.3	5.1					-3.50 / 49	0.3
	TF	RL	YES	092	092.4	4.5			4000	200		1.0
	DF	BH091					R		5000	200		1.0