

RNP RWY 27												
RMK									MAG VAR 2020 0.1°E		REF NAV AID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG		RL										
INA XERGI	IF	XERGI						2500	2500	200		-
	TF	IBH27		183	182.8	6.1		2500	2500	185		1.0
INA BEMAX	IF	BEMAX						3000	3000			-
	TF	IBH27		273	272.7	6.0		2500	2500	185		1.0
INA DEGAX	IF	DEGAX						2500	2500	200		-
	TF	IBH27		003	002.8	6.3		2500	2500	185		1.0
INA RL	IF	RL	YES					2500	FL090	220		-
	TF	BH501		125	125.1	6.5		2500	2500	200		1.0
	TF	BH505		092	092.5	2.7		2500	2500	200		1.0
	TF	IBH27		003	002.8	3.5	L	2500	2500	185		1.0
APCH	IF	IBH27						2500	2500	185		-
	TF	FBH27		272	272.6	4.9		2500	2500			1.0
	TF	RW27	YES	272	272.5	7.0					-3.20 / 45	0.3
	TF	BH512	YES	272	272.4	8.6			2500	220		1.0
	TF	BH514	YES	342	342.3	9.6		4000		220		1.0
	DF	RL					R	2500	FL090	220		1.0