

RNP RWY 21												
RMK	-											
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 0.5°E			REF NAV AID :-	
								MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	BI030	-	-	-	-	-	-	-	-	-	-
INA BI210	IF	BI210	-	-	-	-	-	3000	5000	230	-	-
	TF	BI211	-	211	211.8	11.0	-	3000	3000	185	-	1.0
INA BI212	IF	BI212	-	-	-	-	-	3000	3000	230	-	-
	TF	BI211	-	130	130.4	6.1	-	3000	3000	185	-	1.0
INA BI215	IF	BI215	-	-	-	-	-	3000	3000	230	-	-
	TF	BI211	-	253	253.3	5.0	-	3000	3000	185	-	1.0
INA BI030	IF	BI030	Yes	-	-	-	-	3000	6000	220	-	-
	DF	BI211	-	-	-	-	L	3000	4000	220	-	1.0
	TF	BI213	-	044	045.0	5.0	-	3000	3000	220	-	1.0
	TF	BI215	-	345	346.0	5.4	-	3000	3000	230	-	1.0
	TF	BI211	-	253	253.3	5.0	L	3000	3000	185	-	1.0
APCH	IF	BI211	-	-	-	-	-	3000	3000	185	-	-
	TF	FB211	-	210	210.7	3.5	-	3000	3000	-	-	1.0
	TF	RW21	Yes	210	210.7	8.0	-	-	-	-	-3.00 / 49	0.3
	TF	BI220	Yes	210	210.6	3.0	-	-	2000	185	-	1.0
	DF	BI211	-	-	-	-	L	3000	4000	220	-	1.0
	TF	BI213	-	044	045.0	5.0	-	3000	3000	220	-	1.0
	TF	BI215	-	345	346.0	5.4	-	3000	3000	230	-	1.0