

POITIERS BIARD
STAR RNAV RWY 21
(Codage proposé / *Proposed coding*)

STAR RNAV RWY 21											
RMK	GNSS only						MAG VAR 2020 0.5°E			REF NAVAID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
-	-	BI030	-	-	-			-	-	-	-
VERAC 6H											
-	IF	VERAC	-	-	-			-	-	-	-
-	TF	BI214	-	359	359.8	21.4	-	3000	5000	230	1.0
-	TF	BI212	-	042	042.4	14.7	-	3000	3000	230	1.0
-	TF	IBI21	-	130	130.4	6.1	-	3000	3000	185	1.0
ABSIE 6H											
-	IF	ABSIE	-	-	-			-	-	-	-
-	TF	BI214	-	080	080.5	23.5	-	3000	5000	230	1.0
-	TF	BI212	-	042	042.4	14.7	-	3000	3000	230	1.0
-	TF	IBI21	-	130	130.4	6.1	-	3000	3000	185	1.0
GINON 6H											
-	IF	GINON	-	-	-			-	-	-	-
-	TF	BI212	-	161	161.6	21.4	-	3000	3000	230	1.0
-	TF	IBI21	-	130	130.4	6.1	-	3000	3000	185	1.0
OMARI 6H											
-	IF	OMARI	-	-	-			-	-	-	-
-	TF	BI210	-	211	212.0	17.7	-	3000	5000	-	1.0
-	TF	IBI21	-	211	211.8	11.0	-	3000	3000	185	1.0
OLINO 6H											
-	IF	OLINO	-	-	-			-	-	-	-
-	TF	BI215	-	253	253.7	20.4	-	3000	3000	230	1.0
-	TF	IBI21	-	253	253.3	5.0	-	3000	3000	185	1.0
BALAN 6H											
-	IF	BALAN	-	-	-			-	-	-	-
-	TF	BI215	-	310	310.6	25.0	-	3000	3000	230	1.0
-	TF	IBI21	-	253	253.3	5.0	-	3000	3000	185	1.0