

TOULOUSE BLAGNAC

PRECODING INA RNAV (GNSS) RWY 14R

INA RNAV(GNSS) RWY 14R													
RMK	GNSS only - Linked to FNA RNP 14R and FNA ILS CAT I ou/ or CAT II et/and CAT III ou/ or LOC RWY 14R - Procedure developed under CDO concept							MAG VAR 2020 01.0°E			REF NAV AID :		
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)	
HLDG	-	ADIMO	-	-	-	-	-	-	-	-	-	-	
HLDG	-	FUZAP	-	-	-	-	-	-	-	-	-	-	
HLDG	-	SURAS	-	-	-	-	-	-	-	-	-	-	
INA ADIMO	IF	ADIMO	-	-	-	-	-	FL080	-	-	-	-	
	TF	BO506	-	307	308.2	24.6	-	FL080	-	-	-	1.0	
	TF	BO509	-	307	307.9	11.7	L	4000	-	-	-	1.0	
	TF	IO14R	-	212	212.9	5.0	-	3000	-	210	-	1.0	
INA AGN	IF	AGN	-	-	-	-	-	FL080	-	-	-	-	
	TF	BO508	-	095	096.0	10.3	-	-	-	-	-	1.0	
	TF	IO14R	-	142	142.7	5.7	-	3000	-	210	-	1.0	
INA FUZAP	IF	FUZAP	-	-	-	-	-	FL080	-	-	-	-	
	TF	BO509	-	230	230.8	11.1	-	4000	-	-	-	1.0	
	TF	IO14R	-	212	212.9	5.0	-	3000	-	210	-	1.0	
INA SURAS	IF	SURAS	-	-	-	-	-	FL080	-	-	-	-	
	TF	BO507	-	004	005.2	7.7	-	-	-	-	-	1.0	
	TF	IO14R	-	072	072.8	5.0	-	3000	-	210	-	1.0	