

RNP RWY13												
RMK	-	MAG VAR 2020 1.2°E					REF NAVAID :-					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	ICR13	-	-	-	-	-	-	-	-	-	-
	IF	CR400	-	-	-	-	-	4600	-	200	-	-
INA CR400	TF	ICR13	-	217	218.6	5.0	-	4600	-	185	-	1.0
	IF	CR404	-	-	-	-	-	4600	-	200	-	-
INA CR404	TF	ICR13	-	038	038.9	5.0	-	4600	-	185	-	1.0
APCH	IF	ICR13	-	-	-	-	-	4600	-	-	-	-
	TF	FCR13	-	128	128.8	5.0	-	4600	-	-	-	1.0
	TF	RW13	Yes	128	128.8	7.1	-	-	-	-	-3.50 / 49	0.3
	TF	CR410	-	128	128.9	5.0	-	-	-	-	-	1.0
	TF	CR412	-	218	219.0	5.0	-	-	-	180	-	1.0
	TF	CR404	-	308	308.9	17.1	-	4600	-	200	-	1.0

