

RNP Y RWY 18 (AR)													
RMK	AUTHORIZATION REQUIRED						MAG VAR 2020 2.08°E				REF NAVAIID :		
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	RNP value
HLDG	-	-	PIRUV	-	-	-	-	-	-	-	-	-	-
	IF	-	PIRUV	-	-	-	-	-	6500	6500	210	-	-
INA PIRUV	TF	-	LB501	-	119	121.4	2.7	-	6000	-	-	-	0.8
	TF	-	IB18Y	-	119	121.4	2.1	-	5000	-	170	-	0.8
APCH	IF	-	IB18Y	-	-	-	-	-	5000	-	170	-	0.8
	RF	-	FB18Y	-	-	-	3.1	R	4000	4000	-	-	0.8
	RF	-	LB500	-	-	-	4.8	R	-	-	-	-3.2 / 15	0.3
	TF	-	RW18	YES	175	176.7	4.6	-	-	-	-	-3.2 / 15	0.3
	TF	-	LB510	-	175	176.7	1.7	-	-	-	-	-	0.3
	RF	-	LB511	-	-	-	4.8	R	-	-	-	-	0.3
	TF	-	LB512	-	202	204.0	3.1	-	-	-	-	-	0.3
	RF	-	LB513	-	-	-	5.1	R	-	-	190	-	1.0
	TF	-	BELUS	-	330	332.1	12.6	-	-	-	-	-	1.0
	TF	-	KENZO	-	344	346.4	7.3	-	-	-	-	-	1.0
TF	-	GOVNA	-	006	008.0	5.1	-	-	-	-	-	1.0	
TF	-	PIRUV	-	096	097.9	4.5	-	6500	6500	210	-	1.0	