

CHAMBERY AIX LES BAINS
SID RNAV RWY 18
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 18											
RMK	GNSS seulement / only						MAG VAR 2020 2.1°E			REF NAVAID : VOR-DME CBY	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
VENAT 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	1.0
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	1.0
-	TF	VENAT	-	045	047.1	41.4	-	-	-	-	1.0
ODIKI 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	1.0
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	1.0
-	TF	LB623	-	045	047.1	20.9	-	FL130	-	-	1.0
-	TF	ODIKI	-	131	132.9	6.2	-	FL150	-	220	1.0
ESAPI 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	1.0
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	1.0
-	TF	LB622	-	045	047.1	18.4	-	FL130	-	-	1.0
-	TF	ESAPI	-	141	143.4	7.1	R	FL150	-	220	1.0
PAS 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	1.0
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	1.0
-	TF	PAS	-	011	013.2	23.9	-	-	-	-	1.0
PIRUV 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	BELUS	-	314	316.2	11.5	-	-	-	-	1.0
-	TF	KENZO	-	344	346.3	7.3	-	-	-	-	1.0
-	TF	GOVNA	-	006	008.0	5.1	-	-	-	-	1.0
-	TF	PIRUV	-	096	097.9	4.5	-	-	FL090	210	1.0
BUSIL 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	1.0
-	TF	MAXUS	-	338	340.4	8.2	-	-	-	-	1.0
-	TF	BULOL	-	321	323.5	20.3	-	-	-	-	1.0
-	TF	BUSIL	-	312	314.1	21.4	-	-	-	-	1.0
BULOL 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	1.0
-	TF	MAXUS	-	338	340.4	8.2	-	-	-	-	1.0
-	TF	BULOL	-	321	323.5	20.3	-	-	-	-	1.0
LSE 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	1.0
-	TF	LSE	-	290	292.1	16.2	-	-	-	-	1.0
ROMAM 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	1.0
-	TF	ROMAM	-	198	200.4	34.7	L	-	-	-	1.0
LTP 2R											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	1.0
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	1.0
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	1.0
-	TF	LTP	-	180	182.1	9.3	L	-	-	200	1.0