

LYON SAINT EXUPERY

PRECODING INA RNAV RWY 35L

INA RNAV RWY 35L												
RMK	GNSS seulement/only Associé à/Linked to FNA RNP RWY 35L et/and FNA ILS RWY 35L							MAG VAR 2020	1.9 °E		REF NAVAID : -	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
HLDG	-	ARBON	-	-	-	-	-	-	-	-	-	-
HLDG	-	GOMET	-	-	-	-	-	-	-	-	-	-
HLDG	-	RIPTU	-	-	-	-	-	-	-	-	-	-
HLDG	-	TALAR	-	-	-	-	-	-	-	-	-	-
INA RIPTU3N	IF	RIPTU	-	-	-	-	-	FL070	-	-	-	-
	TF	LL505	-	179	180.6	27.9	-	5000	-	-	-	1.0
	TF	LL503	-	215	216.7	4.0	-	-	-	-	-	1.0
	TF	LL501	-	215	216.7	4.0	-	4000	-	220	-	1.0
	TF	NEGPU	-	264	265.5	4.1	-	3000	4500	220	-	1.0
INA TALAR3N	IF	TALAR	-	-	-	-	-	FL070	-	-	-	-
	TF	LL504	-	152	153.8	24.3	-	-	-	-	-	1.0
	TF	LL502	-	119	121.3	4.0	-	5000	-	-	-	1.0
	TF	LL500	-	119	121.3	4.0	-	4000	-	220	-	1.0
	TF	NEGPU	-	083	085.0	3.9	-	3000	4500	220	-	1.0
INA GOMET3N	IF	GOMET	-	-	-	-	-	FL100	-	-	-	-
	TF	LL513	-	290	291.9	8.6	-	5000	-	-	-	1.0
	TF	LL511	-	290	291.7	4.0	-	-	-	-	-	1.0
	TF	LL510	-	290	291.7	4.0	-	4000	-	220	-	1.0
	TF	NEGPU	-	351	353.2	4.1	-	3000	4500	220	-	1.0
INA ARBON3N	IF	ARBON	-	-	-	-	-	FL070	-	-	-	-
	TF	LL514	-	041	042.5	6.6	-	5000	-	-	-	1.0
	TF	LL512	-	041	042.5	4.0	-	-	-	-	-	1.0
	TF	LL510	-	041	042.6	4.0	-	4000	-	220	-	1.0
	TF	NEGPU	-	351	353.2	4.1	-	3000	4500	220	-	1.0