

LYON SAINT EXUPERY
SID RNAV RWY 17L
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 17L											
RMK	GNSS ou/ or DME/DME (IRU requis/required)						MAG VAR 2020 1.9°E			REF NAVAID : LSE	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
BELUS8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	CF	BELUS	-	072	074.0	-	L	-	FL120	-	1.0
ROMAM8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	TF	ROMAM	-	174	175.5	31.6	-	-	-	-	1.0
MTL8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	TF	ROMAM	-	174	175.5	31.6	-	-	-	-	1.0
-	TF	MTL	-	205	206.6	36.7	-	-	-	-	1.0
LUKUM8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	TF	ROMAM	-	174	175.5	31.6	-	-	-	-	1.0
-	TF	LUKUM	-	174	175.5	10.5	-	-	-	-	1.0
PIMAK8S											
-	CF	LL791	YES	173	175.1	-	-	-	-	-	1.0
-	CA	-	-	173	175.1	-	-	1300	-	-	1.0
-	CF	LL796	YES	235	237.0	-	-	-	-	-	1.0
-	TF	PIMAK	-	253	255.2	38.0	-	-	-	-	1.0
MADOT8S											
-	CF	LL791	YES	173	175.1	-	-	-	-	-	1.0
-	CA	-	-	173	175.1	-	-	1300	-	-	1.0
-	CF	LL796	YES	235	237.0	-	-	-	-	-	1.0
-	TF	MADOT	-	302	304.0	18.7	-	-	-	-	1.0
BELEP8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	CF	LL796	YES	255	257.0	-	-	-	-	-	1.0
-	TF	BELEP	-	292	294.3	34.6	-	-	-	-	1.0
REPSI8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	CF	LL796	YES	255	257.0	-	-	-	-	-	1.0
-	TF	REPSI	-	264	265.7	25.7	-	-	-	-	1.0
MURRO8S											
-	CF	LL793	YES	173	175.1	-	-	-	-	230	1.0
-	CF	MURRO	-	241	243.0	-	-	-	-	-	1.0