

LYON SAINT EXUPERY
STAR RNAV RWY 35L-35R
(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 35L-35R											
RMK	GNSS seulement/only							MAG VAR 2020 1.9°E		REF NAVAIID : LSE	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
HLDG											
ARBON	-	-	-	-	-	-	-	-	-	-	-
GOMET	-	-	-	-	-	-	-	-	-	-	-
TALAR	-	-	-	-	-	-	-	-	-	-	-
RIPTU	-	-	-	-	-	-	-	-	-	-	-
MEZIN 9N											
-	IF	MEZIN	-	-	-	-	-	-	-	-	1.0
-	TF	ROLIR	-	069	071.1	29.1	-	FL070	-	-	1.0
-	TF	ARBON	-	015	016.8	6.8	-	FL070	-	-	1.0
PINED 9N											
-	IF	PINED	-	-	-	-	-	-	-	-	1.0
-	TF	LL103	-	358	359.7	8.3	-	-	FL130	-	1.0
-	TF	OSMAS	-	358	359.6	8.5	-	FL100	-	-	1.0
-	TF	GOMET	-	343	345.1	5.0	-	FL100	-	-	1.0
AMVAR 9N											
-	IF	AMVAR	-	-	-	-	-	-	FL150	-	1.0
-	TF	LL101	-	258	260.4	9.5	-	-	-	-	1.0
-	TF	LL102	-	258	260.2	3.0	-	-	-	-	1.0
-	TF	OSMAS	-	258	260.2	5.5	-	FL100	-	-	1.0
-	TF	GOMET	-	343	345.1	5.0	-	FL100	-	-	1.0
MILPA 9N											
-	IF	MILPA	-	-	-	-	-	-	FL180	-	1.0
-	TF	KUDUP	-	249	251.1	13.4	-	-	-	-	1.0
-	TF	AMKEN	-	249	250.9	8.7	-	-	-	-	1.0
-	TF	RIPTU	-	203	204.9	5.0	-	FL070	-	-	1.0
MTL 9N											
-	IF	MTL	-	-	-	-	-	-	-	-	1.0
-	TF	ROLIR	-	002	004.2	37.3	-	FL070	-	-	1.0
-	TF	ARBON	-	015	016.8	6.8	-	FL070	-	-	1.0
FEDZI 9N											
-	IF	FEDZI	-	-	-	-	-	-	FL190	-	1.0
-	TF	DIRBA	-	125	127.3	35.8	-	-	-	-	1.0
-	TF	TALAR	-	120	121.6	5.0	-	FL070	-	-	1.0
LESPI 9N											
-	IF	LESPI	-	-	-	-	-	-	-	-	1.0
-	TF	DIRBA	-	105	106.5	23.8	-	-	-	-	1.0
-	TF	TALAR	-	120	121.6	5.0	-	FL070	-	-	1.0