

ANNECY MEYTHET
SID RNAV RWY 22
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 22											
RMK	GNSS seulement / only.						MAG VAR 2020 2.1°E			REF NAVAID :	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
VENAT 2A											
-	CF	SOCOF	Yes	217	219.1	4.8	-	-	-	180	1.0
-	DF	LP610	-	-	-	-	R	FL130	-	180	1.0
-	TF	VENAT	-	048	049.7	20.7	-	-	-	-	1.0
ODIKI 2A											
-	CF	SOCOF	Yes	217	219.1	4.8	-	-	-	180	1.0
-	DF	LP610	-	-	-	-	R	FL130	-	180	1.0
-	TF	ODIKI	-	130	131.8	7.1	-	FL150	-	200	1.0
ESAPI 2A											
-	CF	SOCOF	Yes	217	219.1	4.8	-	-	-	180	1.0
-	DF	LP620	-	-	-	-	R	FL130	-	180	1.0
-	TF	ESAPI	-	142	144.0	5.7	-	FL150	-	200	1.0
PAS 2A											
-	CF	SOCOF	Yes	217	219.1	4.8	-	-	-	180	1.0
-	DF	PAS	-	-	-	-	R	-	-	200	1.0
PIRUV 2A											
-	CF	SOCOF	-	217	219.1	4.8	-	-	-	-	1.0
-	TF	IP04X	-	216	217.8	3.5	-	-	-	-	1.0
-	TF	TOLNA	-	216	218.4	10.5	-	-	-	-	1.0
-	TF	BELUS	-	267	268.9	9.2	-	-	-	-	1.0
-	TF	KENZO	-	344	346.3	7.3	-	-	-	-	1.0
-	TF	GOVNA	-	006	008.0	5.1	-	-	-	-	1.0
-	TF	PIRUV	-	096	098.0	4.5	-	-	FL090	210	1.0
LTP 2A											
-	CF	SOCOF	-	217	219.1	4.8	-	-	-	-	1.0
-	TF	TOLNA	-	216	218.4	14.0	-	-	-	250	1.0
-	TF	LTP	-	232	234.4	19.5	-	-	-	-	1.0
BULOL 2A											
-	CF	SOCOF	-	217	219.1	4.8	-	-	-	-	1.0
-	TF	TOLNA	-	216	218.4	14.0	-	-	-	250	1.0
-	TF	BELUS	-	267	268.9	9.2	-	-	-	-	1.0
-	TF	MAXUS	-	301	303.5	10.7	-	-	-	-	1.0
-	TF	BULOL	-	321	323.5	20.3	-	-	-	-	1.0
BUSIL 2A											
-	CF	SOCOF	-	217	219.1	4.8	-	-	-	-	1.0
-	TF	TOLNA	-	216	218.4	14.0	-	-	-	250	1.0
-	TF	BELUS	-	267	268.9	9.2	-	-	-	-	1.0
-	TF	MAXUS	-	301	303.5	10.7	-	-	-	-	1.0
-	TF	BULOL	-	321	323.5	20.3	-	-	-	-	1.0
-	TF	BUSIL	-	312	314.1	21.4	-	-	-	-	1.0
LSE 2A											
-	CF	SOCOF	-	217	219.1	4.8	-	-	-	-	1.0
-	TF	TOLNA	-	216	218.4	14.0	-	-	-	250	1.0
-	TF	BELUS	-	267	268.9	9.2	-	-	-	-	1.0
-	TF	GIRED	-	279	281.4	15.5	-	-	-	-	1.0
-	TF	LSE	-	279	281.2	6.0	-	-	-	-	1.0
ROMAM 2A											
-	CF	SOCOF	-	217	219.1	4.8	-	-	-	-	1.0
-	TF	TOLNA	-	216	218.4	14.0	-	-	-	250	1.0
-	TF	BELUS	-	267	268.9	9.2	-	-	-	-	1.0
-	TF	GIRED	-	279	281.4	15.5	-	-	-	-	1.0
-	TF	ROMAM	-	182	184.4	37.5	L	-	-	-	1.0