

RNP RWY 21												
RMK	-	MAG VAR 2020 0.9°E							REF NAVAID :-			
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	CTX	-	-	-	-	-	-	-	-	-	-
	IF	ROXIL	-	-	-	-	-	3000	5000	-	-	-
	TF	ILX21	-	213	213.5	4.6	-	3000	3000	-	-	1.0
INA CTX	IF	CTX	-	-	-	-	-	3000	3000	220	-	-
	TF	LX212	-	304	305.1	4.7	-	3000	3000	220	-	1.0
	TF	LX214	-	034	035.1	7.6	-	3000	3000	185	-	1.0
	TF	ILX21	-	122	122.9	4.5	-	3000	3000	-	-	1.0
INA LX214	IF	LX214	-	-	-	-	-	3000	3000	185	-	-
	TF	ILX21	-	122	122.9	4.5	-	3000	3000	-	-	1.0
APCH	IF	ILX21	-	-	-	-	-	3000	3000	-	-	-
	TF	FLX21	-	212	213.3	4.5	-	3000	3000	-	-	1.0
	TF	RW21	Yes	212	213.3	7.7	-	-	-	-	-3.00 / 44	0.3
	TF	LX210	Yes	212	213.3	5.0	-	-	-	210	-	1.0
	DF	LX212	-	-	-	-	R	3000	3000	220	-	1.0
	TF	LX214	-	034	035.1	7.6	-	3000	3000	185	-	1.0

↑