

CANNES MANDELIEU
SID RNAV RWY 17
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 17											
RMK	GNSS only						MAG VAR 2020 2.3°E			REF NAVAID : AZR	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy
LONSU 9N											
-	CF	ROLUP	-	155	157.7	-	-	-	-	-	1.0
-	TF	DIMAD	-	129	131.2	17.4	-	-	2000	-	1.0
-	FM	DIMAD	-	129	131.2	-	-	-	-	-	1.0
-	DF	OMARD	-	-	-	-	-	-	-	-	1.0
-	TF	MERLU	-	097	099.4	9.0	-	-	-	-	1.0
-	TF	LONSU	-	148	150.7	20.8	-	-	-	-	1.0
VAREK 9N											
-	CF	ROLUP	-	155	157.7	-	-	-	-	-	1.0
-	TF	DIMAD	-	129	131.2	17.4	-	-	2000	-	1.0
-	FM	DIMAD	-	129	131.2	-	-	-	-	-	1.0
-	DF	OMARD	-	-	-	-	-	-	-	-	1.0
-	TF	VAREK	-	158	159.9	50.5	-	-	-	-	1.0
RUBIT 9N											
-	CF	ROLUP	-	155	157.7	-	-	-	-	-	1.0
-	TF	DIMAD	-	129	131.2	17.4	-	-	2000	-	1.0
-	FM	DIMAD	-	129	131.2	-	-	-	-	-	1.0
-	DF	STP	-	-	-	-	-	4000	-	-	1.0
-	TF	RUBIT	-	269	271.2	8.3	-	-	-	-	1.0
TURIL 9N											
-	CF	ROLUP	-	155	157.7	-	-	-	-	-	1.0
-	TF	DIMAD	-	129	131.2	17.4	-	-	2000	-	1.0
-	FM	DIMAD	-	129	131.2	-	-	-	-	-	1.0
-	DF	STP	-	-	-	-	-	4000	-	-	1.0
-	TF	RUBIT	-	269	271.2	8.3	-	-	-	-	1.0
-	TF	TURIL	-	269	271.0	17.0	-	-	-	-	1.0
LANKO 9N											
-	CF	ROLUP	-	155	157.7	-	-	-	-	-	1.0
-	TF	DIMAD	-	129	131.2	17.4	-	-	2000	-	1.0
-	FM	DIMAD	-	129	131.2	-	-	-	-	-	1.0
-	DF	STP	-	-	-	-	-	4000	-	-	1.0
-	TF	CUERS	-	269	271.3	20.5	-	-	-	-	1.0
-	TF	LANKO	-	269	270.8	5.3	-	-	-	-	1.0