

RNP RWY 06												
RMK	-	MAG VAR 2020 1,19°E						REF NAVAID :-				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG		OA406										
INA OA402	IF	OA402						3100	3100	220		RNAV 1 / RNP APCH
	TF	IOA06		149	150,3	5,0		2600	2600	220		RNAV 1 / RNP APCH
INA OA404	IF	OA404						3100	3100	220		RNAV 1 / RNP APCH
	TF	IOA06		059	060,1	5,0		2600	2600	220		RNAV 1 / RNP APCH
INA OA406	IF	OA406						3500	3500	220		RNAV 1 / RNP APCH
	TF	IOA06		329	330,4	5,0		2600	2600	220		RNAV 1 / RNP APCH
APCH	IF	IOA06						2600	2600	220		RNAV 1 / RNP APCH
	TF	FOA06		059	060,2	5,0		2600	2600			RNP APCH
	TF	RW06	Yes	059	060,3	6,3					-3,0 / 15	RNP APCH
	TF	OA412		059	060,4	6,0			3500	200		RNP APCH
	TF	OA414		146	147,4	13,2		3500	3500	200		RNP APCH
	TF	OA406		264	265,0	19,8		3500	3500	220		RNP APCH