

PRECODING RNP RWY24

RNP RWY 24												
RMK	-	MAG VAR 2020 1,2°E						REF NAV AID : -				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG		OA405										
INA OA401	IF	OA401						3100	3100	220		RNAV 1 / RNP APCH
	TF	IOA24		169	170,4	5,0		2600	2600	220		RNAV 1 / RNP APCH
INA OA403	IF	OA403						3100	3100	220		RNAV 1 / RNP APCH
	TF	IOA24		239	240,6	5,0		2600	2600	220		RNAV 1 / RNP APCH
INA OA405	IF	OA405						3500	3500	220		RNAV 1 / RNP APCH
	TF	IOA24		309	310,5	5,0		2600	2600	220		RNAV 1 / RNP APCH
APCH	IF	IOA24						2600	2600	220		RNAV 1 / RNP APCH
	TF	FOA04		239	240,6	5,0		2600	2600			RNP APCH
	TF	RW24	Yes	239	240,5	6,2					-3,0 / 15	RNP APCH
	TF	OA413	Yes	239	240,4	7,0			3500	200		RNP APCH
	TF	OA415		119	120,4	15,0		3500	3500	200		RNP APCH
	TF	OA405		026	026,8	15,0		3500	3500	220		RNP APCH