

BEAUVAIS TILLE
SID RNAV RWY 12-30
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV Réacteurs / Jets (FL>195) RWY 30 (1T) AGOPA-ERIXU-LATRA-OKASI-PILUL											
RMK	GNSS GNSS ou / or DME/DME. (1) FA ou / or VA acceptable.							MAG VAR 2020 0.9°E		REF NAVAID : BOV	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
AGOPA 1T											
		DEP INI (1)									
	IF	OB701	Yes								RNAV 1
	DF	BSN									RNAV 1
	TF	OB703	Yes	184	184.7	15.1					RNAV 1
	DF	PG101									RNAV 1
	TF	OXCEL		234	234.7	11.3					RNAV 1
	TF	ABOBO		210	210.9	15.4					RNAV 1
	TF	ADADA		209	210.3	14.9					RNAV 1
	TF	AGOPA		178	178.9	12.7					RNAV 1
ERIXU 1T											
		DEP INI (1)									
	IF	OB701	Yes								RNAV 1
	DF	BSN									RNAV 1
	TF	OB703	Yes	184	184.7	15.1					RNAV 1
	DF	PG101									RNAV 1
	TF	OXCEL		234	234.7	11.3					RNAV 1
	TF	ABOBO		210	210.9	15.4					RNAV 1
	TF	EDOXA		176	176.9	13.2					RNAV 1
	TF	ERIXU		170	170.8	12.6					RNAV 1
LATRA 1T											
		DEP INI (1)									
	IF	OB701	Yes								RNAV 1
	DF	BSN									RNAV 1
	TF	OB703	Yes	184	184.7	15.1					RNAV 1
	DF	PG102									RNAV 1
	TF	LAPAX		210	210.7	15.5					RNAV 1
	TF	LALUX		176	177.0	12.8					RNAV 1
	TF	LATRA		159	160.4	12.9					RNAV 1
OKASI 1T											
		DEP INI (1)									
	IF	OB701	Yes								RNAV 1
	DF	BSN									RNAV 1
	TF	OB703	Yes	184	184.7	15.1					RNAV 1
	DF	OSTIP									RNAV 1
	TF	ODEBU		176	177.2	12.5					RNAV 1
	TF	OKASI		152	152.8	13.3					RNAV 1
PILUL 1T											
		DEP INI (1)									
	IF	OB701	Yes								RNAV 1
	DF	BSN									RNAV 1
	TF	OB703	Yes	184	184.7	15.1					RNAV 1
	TF	CLM		184	184.6	5.6					RNAV 1
	TF	MLN		198	198.9	24.7					RNAV 1
	TF	PEKIM		176	177.4	10.8					RNAV 1
	TF	PILUL		141	142.2	14.6					RNAV 1