

PRECODING (GNSS) INA RNAV VEBEK 1W / OKABO 1W RWY 25
PRECODING (GNSS) INA RNAV BANOX 1W / MOPAR 1W RWY 25
PRECODING (GNSS) INA RNAV MOBRO 1W RWY 25

RMK	INA RNAV RWY 25										REF NAV AID : BT	
	(1) Sur instruction ATC uniequemnt / Only on ATC clearance										MAG VAR 2020 1,0°E	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
HLDG	-	LORNI	-	-	-	-	-	-	-	-	-	-
HLDG	-	OKIPA	-	-	-	-	-	-	-	-	-	-
HLDG	-	BANOX	-	-	-	-	-	-	-	-	-	-
HLDG	-	MOPAR	-	-	-	-	-	-	-	-	-	-
INA VEBEK 1W	IF	VEBEK	-	-	-	-	-	FL110	FL110	250	-	1,0
	TF	CTL	-	207	207,9	8,9	-	-	-	-	-	1,0
	TF	PB510	-	224	224,9	7,9	-	-	-	-	-	1,0
	FM	-	-	224	-	-	-	-	-	-	-	-
INA OKABO 1W	IF	OKABO	-	-	-	-	-	FL070	FL070	250	-	1,0
	TF	DOBIK	-	312	313,3	5,7	-	-	-	-	-	1,0
	TF	LIRSO	-	338	339,3	6,2	-	-	-	-	-	1,0
	TF	PB508	-	329	329,9	5,6	-	-	-	-	-	1,0
INA BANOX 1W	FM	-	-	329	-	-	-	-	-	-	-	-
	IF	BANOX	-	-	-	-	-	FL070	FL070	250	-	1,0
	TF	PB502	-	043	043,8	15,4	-	-	-	-	-	1,0
	TF	PB504	-	085	086,5	18,0	-	-	-	-	-	1,0
INA MOPAR 1W (1)	TF	PB506	-	073	074,3	10,7	-	-	-	-	-	1,0
	FM	-	-	073	-	-	-	-	-	-	-	-
	IF	MOPAR	-	-	-	-	-	FL110	FL120	300	-	1,0
	TF	PG534	-	093	093,9	24,8	-	-	-	-	-	1,0
INA MOBRO 1W	TF	CREIL	-	093	094,4	5,0	-	-	-	-	-	1,0
	TF	PG536	-	099	100,1	8,0	-	-	-	-	-	1,0
	FM	-	-	099	-	-	-	-	-	-	-	-
	IF	MOBRO	-	-	-	-	-	FL070	FL070	250	-	1,0
INA	TF	BOV	-	092	092,9	21,4	-	-	-	-	-	1,0
	TF	PG528	-	106	107,2	15,6	-	-	-	-	-	1,0
	FM	-	-	106	-	-	-	-	-	-	-	-