

PARIS LE BOURGET (LFPB)
Réacteurs (R) et hélices (H) / Jets (R) and propellers (H)
 (Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 21											
RMK	GNSS requis / required						MAG VAR 2020 1.0°E			Ref NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
AGOPA 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PB 258	-	-	-	-	-	-	-	-	1.0
-	TF	RBT	-	175	175.7	14.9	-	-	-	-	1.0
-	TF	ADADA	-	178	179.0	21.6	-	-	-	-	1.0
-	TF	AGOPA	-	178	178.9	12.7	-	-	-	280	1.0
ERIXU 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PB 258	-	-	-	-	-	-	-	-	1.0
-	TF	RBT	-	175	175.7	14.9	-	-	-	-	1.0
-	TF	EDOXA	-	157	158.4	23.4	-	-	-	-	1.0
-	TF	ERIXU	-	170	170.8	12.6	-	-	-	280	1.0
LATRA 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PB 256	Yes	-	-	-	-	-	-	-	1.0
-	DF	DEROL	-	-	-	-	-	-	-	-	1.0
-	TF	LALUX	-	152	153.4	26.2	-	-	-	-	1.0
-	TF	LATRA	-	159	160.4	12.9	-	-	-	280	1.0
OKASI 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PB 256	Yes	-	-	-	-	-	-	-	1.0
-	DF	DOPAP	-	-	-	-	-	-	-	-	1.0
-	TF	ODEBU	-	148	148.7	29.5	-	-	-	-	1.0
-	TF	OKASI	-	152	152.8	13.3	-	-	-	280	1.0
PILUL 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PB 256	Yes	-	-	-	-	-	-	-	1.0
-	DF	OXCEL	-	-	-	-	-	-	-	-	1.0
-	TF	PEKIM	-	146	147.3	32.3	-	-	-	-	1.0
-	TF	PILUL	-	141	142.2	14.6	-	-	-	280	1.0
LGL 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PG 286	-	-	-	-	-	-	-	-	1.0
-	TF	LESGA	-	264	264.8	43.2	-	-	-	-	1.0
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	1.0
ELCOB 6P											
-	CA	-	-	204	204.8	-	-	550	-	-	1.0
-	DF	PB 253	Yes	-	-	-	-	-	-	205	1.0
-	DF	PG 286	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	279	279.7	26.9	-	-	-	-	1.0