

PARIS LE BOURGET (LFPB)
Réacteurs (R) et hélices (H) / Jets (R) and propellers (H)
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 25											
RMK	GNSS ou / or DME/DME						MAG VAR 2020 1.0°E			Ref NAVAIID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
OKASI 6F											
-	CA	-	-	245	246.2	-	-	600	-	-	1.0
-	CF	PB 253	Yes	245	246.2	-	-	-	-	-	1.0
-	DF	PB 256	Yes	-	-	-	-	-	-	-	1.0
-	DF	DOPAP	-	-	-	-	L	-	-	-	1.0
-	TF	ODEBU	-	148	148.7	29.5	-	-	-	-	1.0
-	TF	OKASI	-	152	152.8	13.3	-	-	-	280	1.0
PILUL 6F											
-	CA	-	-	245	246.2	-	-	600	-	-	1.0
-	CF	PB 253	Yes	245	246.2	-	-	-	-	-	1.0
-	DF	PB 256	Yes	-	-	-	-	-	-	-	1.0
-	DF	OXCEL	-	-	-	-	L	-	-	-	1.0
-	TF	PEKIM	-	146	147.3	32.3	-	-	-	-	1.0
-	TF	PILUL	-	141	142.2	14.6	-	-	-	280	1.0
LGL 6C											
-	CA	-	-	245	246.2	-	-	600	-	-	1.0
-	CF	PB 253	Yes	245	246.2	-	-	-	-	-	1.0
-	DF	PG 286	-	-	-	-	-	-	-	-	1.0
-	TF	LESGA	-	264	264.8	43.2	-	-	-	-	1.0
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	1.0
ELCOB 6C											
-	CA	-	-	245	246.2	-	-	600	-	-	1.0
-	CF	PB 253	Yes	245	246.2	-	-	-	-	-	1.0
-	DF	PG 286	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	279	279.7	26.9	-	-	-	-	1.0
LGL 6F											
-	CA	-	-	245	246.2	-	-	600	-	-	1.0
-	CF	PB 253	Yes	245	246.2	-	-	-	-	-	1.0
-	DF	PG 286	-	-	-	-	-	-	-	-	1.0
-	TF	LESGA	-	264	264.8	43.2	-	-	-	-	1.0
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	1.0
ELCOB 6F											
-	CA	-	-	245	246.2	-	-	600	-	-	1.0
-	CF	PB 253	Yes	245	246.2	-	-	-	-	-	1.0
-	DF	PG 286	-	-	-	-	-	-	-	-	1.0
-	TF	ELCOB	-	279	279.7	26.9	-	-	-	-	1.0