

PARIS LE BOURGET (LFPB)
Réacteurs (R) et hélices (H) / Jets (R) and propellers (H)
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 25											
RMK	GNSS ou / or DME/DME						MAG VAR 2020 1.0°E			Ref NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
→	DORDI 6C										
→	-	CA	-	-	245	246.2	-	600	-	-	1.0
→	-	CF	PB253	Yes	245	246.2	-	-	-	-	1.0
→	-	TF	PB259	Yes	245	245.9	3.6	-	-	-	1.0
→	-	DF	PB260	-	-	-	L	-	-	-	1.0
→	-	TF	OXCEL	-	123	124.5	10.6	-	-	-	1.0
→	-	TF	DORDI	-	151	152.2	34.6	-	-	220	1.0
→	DORDI 6F										
→	-	CA	-	-	245	246.2	-	600	-	-	1.0
→	-	CF	PB253	Yes	245	246.2	-	-	-	-	1.0
→	-	TF	PB259	Yes	245	245.9	3.6	-	-	-	1.0
→	-	DF	PB260	-	-	-	L	-	-	-	1.0
→	-	TF	OXCEL	-	123	124.5	10.6	-	-	-	1.0
→	-	TF	DORDI	-	151	152.2	34.6	-	-	220	1.0
→	MONOT 6C										
→	-	CA	-	-	245	246.2	-	600	-	-	1.0
→	-	CF	PB253	Yes	245	246.2	-	-	-	-	1.0
→	-	TF	PB259	Yes	245	245.9	3.6	-	-	-	1.0
→	-	DF	PB260	-	-	-	L	-	-	-	1.0
→	-	TF	OXCEL	-	123	124.5	10.6	-	-	-	1.0
→	-	TF	PB277	-	187	188.3	22.2	-	-	-	1.0
→	-	TF	MONOT	-	160	160.6	17.9	-	-	220	1.0
→	MONOT 6F										
→	-	CA	-	-	245	246.2	-	600	-	-	1.0
→	-	CF	PB253	Yes	245	246.2	-	-	-	-	1.0
→	-	TF	PB259	Yes	245	245.9	3.6	-	-	-	1.0
→	-	DF	PB260	-	-	-	L	-	-	-	1.0
→	-	TF	OXCEL	-	123	124.5	10.6	-	-	-	1.0
→	-	TF	MONOT	-	175	176.0	38.9	-	-	220	1.0
→	OLZOM 6C										
→	-	CA	-	-	245	246.2	-	600	-	-	1.0
→	-	CF	PB253	Yes	245	246.2	-	-	-	-	1.0
→	-	TF	PB259	Yes	245	245.9	3.6	-	-	-	1.0
→	-	DF	PB260	-	-	-	L	-	-	-	1.0
→	-	TF	OXCEL	-	123	124.5	10.6	-	-	-	1.0
→	-	TF	OLZOM	-	187	188.3	34.9	-	-	220	1.0
→	OLZOM 6F										
→	-	CA	-	-	245	246.2	-	600	-	-	1.0
→	-	CF	PB253	Yes	245	246.2	-	-	-	-	1.0
→	-	TF	PB259	Yes	245	245.9	3.6	-	-	-	1.0
→	-	DF	PB260	-	-	-	L	-	-	-	1.0
→	-	TF	OXCEL	-	123	124.5	10.6	-	-	-	1.0
→	-	TF	OLZOM	-	187	188.3	34.9	-	-	220	1.0