

PRECODING INA RNAV LORNI-VEBEK-OKIPA-BANOX-MOPAR-MOBRO RWY 26L

INA RNAV RWY 26L												
RMK	(1) Réacteurs / Jets = (R) - Hélices / Propellers = (H)							MAG VAR 2020 1.1°E			REF NAV AID : BT	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
HLDG	-	LORNI	-	-	-	-	-	-	-	-	-	-
HLDG	-	OKIPA	-	-	-	-	-	-	-	-	-	-
HLDG	-	BANOX	-	-	-	-	-	-	-	-	-	-
HLDG	-	MOPAR	-	-	-	-	-	-	-	-	-	-
INA LORNI 1W	IF	LORNI	-	-	-	-	-	FL070	FL130	250	-	1,0
	TF	PG520	-	208	209,5	10,0	-	-	-	-	-	1,0
	FM	-	-	208	-	-	-	-	-	-	-	-
INA NIGHT LORNI 3Y	IF	LORNI	-	-	-	-	-	FL070	FL130	250	-	1,0
	TF	PG520	-	208	209,5	10,0	-	-	-	-	-	1,0
	TF	PG562	-	216	216,7	11,9	-	FL070	-	-	-	1,0
INA VEBEK 1W	TF	IG26L	-	230	230,7	9,6	-	4000	-	185	-	1,0
	IF	VEBEK	-	-	-	-	-	FL080	FL110	250	-	1,0
	TF	CTL	-	207	207,9	8,9	-	-	-	-	-	1,0
INA OKIPA 1W	FM	-	-	224	-	-	-	-	-	-	-	-
	IF	OKIPA	-	-	-	-	-	FL070 (R) (1) FL070 (H) (1)	FL110 (R) (1) FL100 (H) (1)	250	-	1,0
	TF	PG522	-	329	330,1	12,0	-	-	-	-	-	1,0
INA NIGHT OKIPA 3Y	FM	-	-	329	-	-	-	-	-	-	-	-
	IF	OKIPA	-	-	-	-	-	FL070 (R) (1) FL070 (H) (1)	FL110 (R) (1) FL100 (H) (1)	250	-	1,0
	TF	PG522	-	329	330,1	12,0	-	FL070	-	-	-	1,0
INA BANOX 1W	TF	PG564	-	329	330,0	11,5	-	-	-	-	-	1,0
	TF	IG26L	-	286	287,1	12,8	-	4000	-	185	-	1,0
	IF	BANOX	-	-	-	-	-	FL140 (R) (1) FL140 (H) (1)	FL150 (R) (1) FL140 (H) (1)	300	-	1,0
INA BANOX 1X	TF	DOMUS	-	043	043,8	26,2	-	-	-	-	-	1,0
	TF	PG510	-	084	084,9	9,9	-	-	-	-	-	1,0
	TF	PG515	-	084	085,1	9,8	-	-	-	-	-	1,0
INA NIGHT BANOX 3Y	TF	PG516	-	088	088,9	8,0	-	-	-	-	-	1,0
	TF	PG517	Y	088	089,1	13,5	-	-	-	-	-	1,0
	FM	-	-	088	-	-	-	-	-	-	-	-
INA MOPAR 1W	IF	BANOX	-	-	-	-	-	FL170	FL180	300	-	1,0
	TF	DOMUS	-	043	043,8	26,2	-	FL140	FL160	-	-	1,0
	TF	PG510	-	084	084,9	9,9	-	FL130	FL140	250	-	1,0
INA NIGHT MOPAR 3Y	TF	PG515	-	084	085,1	9,8	-	-	-	-	-	1,0
	TF	PG516	-	088	088,9	8,0	-	-	-	-	-	1,0
	TF	PG517	Y	088	089,1	13,5	-	-	-	-	-	1,0
INA MOBRO 1W	FM	-	-	088	-	-	-	-	-	-	-	-
	IF	BANOX	-	-	-	-	-	-	-	300	-	1,0
	TF	DOMUS	-	043	043,8	26,2	-	FL140	FL150	-	-	1,0
INA NIGHT MOBRO 3Y	TF	PG510	-	084	084,9	9,9	-	FL130	FL140	250	-	1,0
	TF	PG515	-	084	085,1	9,8	-	-	-	-	-	1,0
	TF	PG566	-	103	104,1	11,0	-	FL070	-	-	-	1,0
INA MOPAR 1X	TF	PG568	-	084	085,5	11,0	-	-	-	220	-	1,0
	TF	IG26L	-	345	345,6	7,9	-	4000	-	185	-	1,0
	IF	MOPAR	-	-	-	-	-	FL110	FL120	300	-	1,0
INA NIGHT MOPAR 3Y	TF	PG534	-	093	093,9	24,8	-	-	-	-	-	1,0
	TF	CREIL	-	093	094,4	5,0	-	-	-	-	-	1,0
	TF	PG536	-	099	100,1	8,0	-	-	-	-	-	1,0
INA MOBRO 1W	FM	-	-	099	-	-	-	-	-	-	-	-
	IF	MOPAR	-	-	-	-	-	FL150	FL160	300	-	1,0
	TF	PG534	-	093	093,9	24,8	-	-	-	-	-	1,0
INA NIGHT MOBRO 3Y	TF	CREIL	-	093	094,4	5,0	-	FL110	FL120	250	-	1,0
	TF	PG536	-	099	100,1	8,0	-	-	-	-	-	1,0
	TF	PG560	-	099	100,3	10,1	-	FL070	-	-	-	1,0
INA MOBRO 1X	TF	IG26L	-	181	182,3	11,3	-	4000	-	185	-	1,0
	IF	MOBRO	-	-	-	-	-	FL070 (H) (1)	FL070 (H) (1)	250	-	1,0
	TF	BOV	-	092	092,9	21,4	-	-	-	-	-	1,0
INA NIGHT MOBRO 3Y	TF	PG528	-	106	107,2	15,6	-	-	-	-	-	1,0
	FM	-	-	106	-	-	-	-	-	-	-	-
	IF	MOBRO	-	-	-	-	-	FL070 (H) (1)	FL070 (H) (1)	250	-	1,0
INA MOBRO 1W	TF	BOV	-	092	092,9	21,4	-	-	-	-	-	1,0
	TF	PG528	-	106	107,2	15,6	-	-	-	-	-	1,0
	TF	PG560	-	118	118,8	19,5	-	FL070	-	-	-	1,0
INA NIGHT MOBRO 3Y	TF	IG26L	-	181	182,3	11,3	-	4000	-	185	-	1,0