

INA RNAV RWY 28												
RMK	-					MAG VAR 2020 1.1°E			REF NAVAID :-			
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	ATTUC	-	-	-	-	-	-	-	-	-	-
	-	MLN	-	-	-	-	-	-	-	-	-	-
	-	VANEX	-	-	-	-	-	-	-	-	-	-
INA ATTUC	IF	ATTUC	-	-	-	-	-	3000	5000	-	-	1.0
	TF	PM501	-	321	322.4	12.4	-	-	3000	-	-	1.0
	TF	VANEX	-	285	285.6	4.7	-	2000	2000	-	-	1.0
	TF	IPM28	-	284	285.5	3.7	-	2000	-	170	-	1.0
INA NERIN	IF	NERIN	-	-	-	-	-	2000	-	170	-	1.0
	TF	IPM28	-	213	213.7	5.0	-	2000	-	170	-	1.0
	IF	MLN	-	-	-	-	-	2000	-	170	-	1.0
INA MLN	TF	PM500	-	047	048.1	4.6	-	2000	-	170	-	1.0
	TF	IPM28	-	353	353.7	3.9	-	2000	-	170	-	1.0

↑ ↑ ↓ ↓ ↓ ↓ ↑ ↑ ↑ ↑ ↓ ↓