

MELUN VILLAROCHE
PRECODING RNP Y RWY 28

RNP Y RWY 28													
RMK	-								MAG VAR 2020 1.1°E			REF NAVAD :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)	
HLDG	-	ATTUC	-	-	-	-	-	-	-	-	-	-	
	-	ADDOZ	-	-	-	-	-	-	-	-	-	-	
INA ATTUC	-	VANEX	-	-	-	-	-	-	-	-	-	-	
	IF	ATTUC	-	-	-	-	-	3000	5000	-	-	1.0	
	TF	PM501	-	321	322.4	12.4	-	-	3000	-	-	1.0	
	TF	VANEX	-	285	285.6	4.7	-	2000	2000	220	-	1.0	
	TF	IPM28	-	284	285.5	3.7	-	2000	-	170	-	1.0	
INA APOC	IF	APOC	-	-	-	-	-	-	-	-	-	1.0	
	TF	PM505	-	282	283.5	5.9	-	-	4000	-	-	1.0	
	TF	PM504	-	282	283.4	3.0	-	-	3000	-	-	1.0	
	TF	VANEX	-	282	283.4	5.4	-	2000	2000	220	-	1.0	
	TF	IPM28	-	284	285.5	3.7	-	2000	-	170	-	1.0	
INA ADDOZ	IF	ADDOZ	-	-	-	-	-	2000	2000	-	-	1.0	
	TF	PM500	-	039	040.6	5.3	-	-	-	-	-	1.0	
	TF	IPM28	-	352	353.6	3.9	-	2000	-	170	-	1.0	
INA NERIN	IF	NERIN	-	-	-	-	-	2000	-	-	-	1.0	
	TF	IPM28	-	213	213.8	5.0	-	2000	-	170	-	1.0	
INA VANEX	IF	VANEX	-	-	-	-	-	2000	2000	220	-	1.0	
	TF	IPM28	-	284	285.5	3.7	-	2000	-	170	-	1.0	
APCH	IF	IPM28	-	-	-	-	-	2000	-	170	-	1.0	
	TF	FPM28	-	282	283.7	3.0	-	2000	2000	160	-	1.0	
	TF	RW28	Y	282	283.6	5.2	-	-	-	-	-3.0 / 50	0.3	
	TF	PM519	Y	282	283.5	4.1	-	-	-	160	-	1.0	
	DF	PM520	-	-	-	-	L	-	-	180	-	1.0	
	TF	PM521	-	196	196.8	3.8	-	2000	2000	180	-	1.0	
	TF	NIMLA	-	133	134.2	5.3	-	-	-	-	-	1.0	
TF	ADDOZ	-	101	102.3	8.9	-	2000	2000	-	-	1.0		
	TF	ATTUC	-	101	102.5	19.2	-	3000	5000	-	-	1.0	

← ↑

↑ ↑ ↑ ↑ ↑

← ← ← ↑ ↑