

PARIS SACLAY VERSAILLES (LFPN)
SID RNAV RWY 07L (2A - 2B)
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 07L											
RMK							MAG VAR 2020 1.0°E			Ref NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
OLZOM 2A											
-	CA	-	-	070	071.2	-	-	910	-	-	1.0
-	CF	PN070	Yes	075	075.8	-	-	-	-	-	1.0
-	TF	PN071	-	075	075.9	7.2	-	-	-	-	1.0
-	TF	OXCEL	Yes	160	161.0	4.2	R	-	-	-	1.0
-	DF	OLZOM	-	-	-	-	-	-	-	-	1.0
MONOT 2A											
-	CA	-	-	070	071.2	-	-	910	-	-	1.0
-	CF	PN070	Yes	075	075.8	-	-	-	-	-	1.0
-	TF	PN071	-	075	075.9	7.2	-	-	-	-	1.0
-	TF	OXCEL	Yes	160	161.0	4.2	R	-	-	-	1.0
-	DF	MONOT	-	-	-	-	-	-	-	-	1.0
DORDI 2A											
-	CA	-	-	070	071.2	-	-	910	-	-	1.0
-	CF	PN070	Yes	075	075.8	-	-	-	-	-	1.0
-	TF	PN072	Yes	075	075.9	13.8	-	-	-	-	1.0
-	DF	PN076	-	-	-	-	-	-	-	-	1.0
-	TF	MLN	-	181	181.5	19.8	-	-	-	-	1.0
-	TF	DORDI	-	183	183.5	14.2	-	-	-	-	1.0
OLZOM 2B											
-	CA	-	-	070	071.2	-	-	910	-	-	1.0
-	CF	PN070	Yes	075	075.8	-	-	-	-	-	1.0
-	TF	PN071	-	075	075.9	7.2	-	-	-	-	1.0
-	TF	OXCEL	Yes	160	161.0	4.2	R	-	-	-	1.0
-	DF	OLZOM	-	-	-	-	-	-	-	-	1.0
MONOT 2B											
-	CA	-	-	070	071.2	-	-	910	-	-	1.0
-	CF	PN070	Yes	075	075.8	-	-	-	-	-	1.0
-	TF	PN071	-	075	075.9	7.2	-	-	-	-	1.0
-	TF	OXCEL	Yes	160	161.0	4.2	R	-	-	-	1.0
-	DF	MONOT	-	-	-	-	-	-	-	-	1.0
DORDI 2B											
-	CA	-	-	070	071.2	-	-	910	-	-	1.0
-	CF	PN070	Yes	075	075.8	-	-	-	-	-	1.0
-	TF	PN072	Yes	075	075.9	13.8	-	-	-	-	1.0
-	DF	PN076	-	-	-	-	-	-	-	-	1.0
-	TF	MLN	-	181	181.5	19.8	-	-	-	-	1.0
-	TF	DORDI	-	183	183.5	14.2	-	-	-	-	1.0