

PARIS SACLAY VERSAILLES (LFPN)
SID RNAV RWY 25R (2P - 2V)
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 25R											
RMK							MAG VAR 2020 1,0°E			REF NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
OPALE 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO262	-	-	-	-	-	-	-	-	1.0
-	TF	BOV	-	021	022.1	13.2	-	-	-	-	1.0
-	TF	OPALE	-	339	339.5	29.7	-	-	-	-	1.0
ATREX 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO262	-	-	-	-	-	-	-	-	1.0
-	TF	BOV	-	021	022.1	13.2	-	-	-	-	1.0
-	TF	ATREX	-	021	021.8	22.6	-	-	-	-	1.0
NURMO 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO262	-	-	-	-	-	-	-	-	1.0
-	TF	EGOZE	-	042	043.3	26.4	-	-	-	-	1.0
-	TF	NURMO	-	031	032.1	19.4	-	-	-	-	1.0
OPALE 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	PO302	-	083	084.3	27.1	-	-	-	-	1.0
-	TF	PO304	-	048	048.8	11.5	-	-	-	-	1.0
-	TF	PO306	-	013	014.1	13.7	-	-	-	-	1.0
-	TF	PB096	-	331	332.1	18.1	-	-	-	-	1.0
-	TF	OPALE	-	318	318.5	61.6	-	-	-	-	1.0
ATREX 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	PO302	-	083	084.3	27.1	-	-	-	-	1.0
-	TF	PO304	-	048	048.8	11.5	-	-	-	-	1.0
-	TF	PO306	-	013	014.1	13.7	-	-	-	-	1.0
-	TF	PB096	-	331	332.1	18.1	-	-	-	-	1.0
-	TF	ATREX	-	329	330.4	44.9	-	-	-	-	1.0
NURMO 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	PO302	-	083	084.3	27.1	-	-	-	-	1.0
-	TF	PO304	-	048	048.8	11.5	-	-	-	-	1.0
-	TF	PO306	-	013	014.1	13.7	-	-	-	-	1.0
-	TF	PB096	-	331	332.1	18.1	-	-	-	-	1.0
-	TF	NURMO	-	349	350.3	42.0	-	-	-	-	1.0