

PARIS SACLAY VERSAILLES (LFPN)
SID RNAV RWY 25R (2P - 2V)
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 25R											
RMK							MAG VAR 2020 1,0°E			REF NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
AGOPA 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO271	-	-	-	-	-	-	FL 100	-	1.0
-	TF	ADADA	-	180	181.0	11.2	-	-	-	-	1.0
-	TF	AGOPA	-	178	178.9	12.7	-	-	-	-	1.0
ERIXU 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO271	-	-	-	-	-	-	FL 100	-	1.0
-	TF	EDOXA	-	144	144.9	14.0	-	-	-	-	1.0
-	TF	ERIXU	-	170	170.8	12.6	-	-	-	-	1.0
LATRA 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	LALUX	-	140	141.2	15.0	-	-	-	-	1.0
-	TF	LATRA	-	159	160.4	12.9	-	-	-	-	1.0
OKASI 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	ODEBU	-	122	123.4	21.7	-	-	-	-	1.0
-	TF	OKASI	-	152	152.8	13.3	-	-	-	-	1.0
PILUL 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	PEKIM	-	114	115.1	28.8	-	-	-	-	1.0
-	TF	PILUL	-	141	142.2	14.6	-	-	-	-	1.0
AGOPA 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO271	-	-	-	-	-	-	FL 100	-	1.0
-	TF	ADADA	-	180	181.0	11.2	-	-	-	-	1.0
-	TF	AGOPA	-	178	178.9	12.7	-	-	-	-	1.0
ERIXU 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	DF	PO271	-	-	-	-	-	-	FL 100	-	1.0
-	TF	EDOXA	-	144	144.9	14.0	-	-	-	-	1.0
-	TF	ERIXU	-	170	170.8	12.6	-	-	-	-	1.0
LATRA 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	LALUX	-	140	141.2	15.0	-	-	-	-	1.0
-	TF	LATRA	-	159	160.4	12.9	-	-	-	-	1.0
OKASI 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	ODEBU	-	122	123.4	21.7	-	-	-	-	1.0
-	TF	OKASI	-	152	152.8	13.3	-	-	-	-	1.0
PILUL 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN290	-	-	-	-	-	-	FL 100	-	1.0
-	TF	PEKIM	-	114	115.1	28.8	-	-	-	-	1.0
-	TF	PILUL	-	141	142.2	14.6	-	-	-	-	1.0