

PARIS SACLAY VERSAILLES (LFPN)
SID RNAV RWY 25R (2P - 2V)
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 25R											
RMK	-						MAG VAR 2020 1,0°E			REF NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
OLZOM 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	OLZOM	-	-	-	-	-	-	-	-	1.0
MONOT 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	MONOT	-	-	-	-	-	-	-	-	1.0
DORDI 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN251	-	-	-	-	-	-	-	-	1.0
-	TF	PN252	-	090	090.5	18.1					1.0
-	TF	DORDI	-	151	152.3	16.1					1.0
OLZOM 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	OLZOM	-	-	-	-	-	-	-	-	1.0
MONOT 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	MONOT	-	-	-	-	-	-	-	-	1.0
DORDI 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	RBT	Yes	159	160.0	5.2	L	-	-	-	1.0
-	DF	PN251	-	-	-	-	-	-	-	-	1.0
-	TF	PN252	-	090	090.5	18.1					1.0
-	TF	DORDI	-	151	152.3	16.1					1.0