

PARIS SACLAY VERSAILLES (LFPN)
SID RNAV 25R (2P - 2V)
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 25R											
RMK	-						MAG VAR 2020 1,0°E			REF NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
ELCOB 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	TF	PO191	-	274	274.7	13.3	-	-	-	-	1.0
-	TF	ELCOB	-	327	328.4	20.0	-	-	-	-	1.0
LGL 2P											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	TF	PO191	-	274	274.7	13.3	-	-	-	-	1.0
-	TF	LGL	-	273	274.2	38.0	-	-	-	-	1.0
ELCOB 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	TF	PN256	-	274	274.7	7.4	-	-	5000	-	1.0
-	TF	PO191	-	274	274.6	5.9	-	-	-	-	1.0
-	TF	ELCOB	-	327	328.4	20.0	-	-	-	-	1.0
LGL 2V											
-	CF	PN250	-	260	261.0	-	-	-	-	-	1.0
-	TF	HOL	Yes	266	266.8	5.1	-	-	-	-	1.0
-	TF	PN256	-	274	274.7	7.4	-	-	5000	-	1.0
-	TF	PO191	-	274	274.6	5.9	-	-	-	-	1.0
-	TF	LGL	-	273	274.2	38.0	-	-	-	-	1.0