

PARIS ORLY (LFPO)
Réacteurs (R) et hélices (H) / Jets (R) and Propellers (H)
OPALE - ATREX - NURMO - OKASI - PILUL - ELCOB - LGL - DIKOL - BAXIR
RANUX - BUBLI - AGOPA - ERIXU - LATRA - OLZOM - MONOT - DORDI
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 20											
RMK	GNSS ou/or DME/DME						MAG VAR 2020 1.0°E			Ref NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
ELCOB 2Y											
-	CA	-	-	197	198.4	-	-	700	-	-	1.0
-	CF	PO202	Yes	225	225.9	-	-	-	-	-	1.0
-	DF	PO204	Yes	-	-	-	-	-	-	-	1.0
-	DF	PO189	-	-	-	-	-	-	-	-	1.0
-	TF	PO191	-	286	287.5	17.0	-	-	-	-	1.0
-	TF	ELCOB	-	327	328.4	20.0	-	-	-	-	1.0
LGL 2Y											
-	CA	-	-	197	198.4	-	-	700	-	-	1.0
-	CF	PO202	Yes	225	225.9	-	-	-	-	-	1.0
-	DF	PO204	Yes	-	-	-	-	-	-	-	1.0
-	DF	PO189	-	-	-	-	-	-	-	-	1.0
-	TF	PO191	-	286	287.5	17.0	-	-	-	-	1.0
-	TF	LGL	-	273	274.2	38.0	-	-	-	-	1.0
ELCOB 2S											
-	CA	-	-	197	198.4	-	-	700	-	-	1.0
-	CF	PO202	Yes	225	225.9	-	-	-	-	-	1.0
-	DF	PO204	Yes	-	-	-	-	-	-	-	1.0
-	DF	PO189	-	-	-	-	-	-	-	-	1.0
-	TF	PO191	-	286	287.5	17.0	-	-	-	-	1.0
-	TF	ELCOB	-	327	328.4	20.0	-	-	-	-	1.0
LGL 2S											
-	CA	-	-	197	198.4	-	-	700	-	-	1.0
-	CF	PO202	Yes	225	225.9	-	-	-	-	-	1.0
-	DF	PO204	Yes	-	-	-	-	-	-	-	1.0
-	DF	PO189	-	-	-	-	-	-	-	-	1.0
-	TF	PO191	-	286	287.5	17.0	-	-	-	-	1.0
-	TF	LGL	-	273	274.2	38.0	-	-	-	-	1.0