

PARIS ORLY (LFPO)
Réacteurs (R) et hélices (H) / Jets (R) and Propellers (H)
OPALE - ATREX - NURMO - OKASI - PILUL - ELCOB - LGL - DIKOL - BAXIR
RANUX - BUBLI - AGOPA - ERIXU - LATRA - OLZOM - MONOT - DORDI
 (Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 24											
RMK	GNSS ou/ou DME/DME						MAG VAR 2020 1.0°E			Ref NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
LATRA 2W											
-	CF	PO244	Yes	236	237,2	-	-	-	-	-	1,0
-	DF	PO301	-	-	-	-	-	-	FL 100	-	1,0
-	TF	LALUX	-	161	162,1	12,1	-	-	-	-	1,0
-	TF	LATRA	-	159	160,4	12,9	-	-	-	-	1,0
OKASI 2W											
-	CF	PO243	Yes	236	237,2	-	-	-	-	-	1,0
-	DF	PO300	-	-	-	-	-	-	FL 100	-	1,0
-	TF	ODEBU	-	140	140,9	16,4	-	-	-	-	1,0
-	TF	OKASI	-	152	152,8	13,3	-	-	-	-	1,0
PILUL 2W											
-	CF	PO243	Yes	236	237,2	-	-	-	-	-	1,0
-	DF	PO300	-	-	-	-	-	-	FL 100	-	1,0
-	TF	PEKIM	-	124	125,4	22,5	-	-	-	-	1,0
-	TF	PILUL	-	141	142,2	14,6	-	-	-	-	1,0
AGOPA 2Q											
-	CF	PO246	Yes	236	237,1	-	-	-	-	-	1,0
-	DF	PO271	-	-	-	-	-	-	FL 100	-	1,0
-	TF	ADADA	-	180	181,0	11,2	-	-	-	-	1,0
-	TF	AGOPA	-	178	178,9	12,7	-	-	-	-	1,0
ERIXU 2Q											
-	CF	PO246	Yes	236	237,1	-	-	-	-	-	1,0
-	DF	PO270	-	-	-	-	-	-	-	-	1,0
-	TF	PO303	-	156	157,5	4,0	-	-	FL 100	-	1,0
-	TF	EDOXA	-	156	157,5	11,8	-	-	-	-	1,0
-	TF	ERIXU	-	170	170,8	12,6	-	-	-	-	1,0
LATRA 2Q											
-	CF	PO244	Yes	236	237,2	-	-	-	-	-	1,0
-	DF	PO301	-	-	-	-	-	-	FL 100	-	1,0
-	TF	LALUX	-	161	162,1	12,1	-	-	-	-	1,0
-	TF	LATRA	-	159	160,4	12,9	-	-	-	-	1,0
OKASI 2Q											
-	CF	PO243	Yes	236	237,2	-	-	-	-	-	1,0
-	DF	PO300	-	-	-	-	-	-	FL 100	-	1,0
-	TF	ODEBU	-	140	140,9	16,4	-	-	-	-	1,0
-	TF	OKASI	-	152	152,8	13,3	-	-	-	-	1,0
PILUL 2Q											
-	CF	PO243	Yes	236	237,2	-	-	-	-	-	1,0
-	DF	PO300	-	-	-	-	-	-	FL 100	-	1,0
-	TF	PEKIM	-	124	125,4	22,5	-	-	-	-	1,0
-	TF	PILUL	-	141	142,2	14,6	-	-	-	-	1,0