

PARIS ORLY
Réacteurs et Hélices / Jets and Propellers
(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 20											
RMK	GNSS - DME/DME						MAG VAR 2020 1,0°E			REF NAVAID :	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
NIMER 9W	(UIR)										
	IF	NIMER	-	-	-	-	-	-	-	-	1,0
	TF	SOMED	-	094	095,1	23,9	-	-	FL260	280	1,0
	TF	DIBES	-	056	056,9	7,9	-	-	-	-	1,0
	TF	CAD	-	018	018,9	35,0	-	FL130	FL130	-	1,0
	TF	SOTIP	-	033	034,0	5,2	-	-	FL130	-	1,0
	TF	ODILO	-	033	034,1	8,0	-	FL110	FL110	-	1,0
AMB 9W	(UIR FIR)										
	IF	AMB	-	-	-	-	-	-	FL260	280	1,0
	TF	DIBES	-	018	019,2	5,0	-	-	-	-	1,0
	TF	CAD	-	018	018,9	35,0	-	FL130	FL130	-	1,0
	TF	SOTIP	-	033	034,0	5,2	-	-	FL130	-	1,0
	TF	ODILO	-	033	034,1	8,0	-	FL110	FL110	-	1,0
LUMAN 9W	(FIR)										
	IF	LUMAN	-	-	-	-	-	-	-	280	1,0
	TF	CAD	-	078	079,3	39,9	-	FL130	FL130	-	1,0
	TF	SOTIP	-	033	034,0	5,2	-	-	FL130	-	1,0
	TF	ODILO	-	033	034,1	8,0	-	FL110	FL110	-	1,0
BOBSA 9W	(FIR)										
	IF	BOBSA	-	-	-	-	-	-	-	-	1,0
	TF	BENAR	-	164	165,2	15,1	-	FL130	FL130	280	1,0
	TF	CAD	-	113	114,0	28,3	-	FL130	FL130	-	1,0
	TF	SOTIP	-	033	034,0	5,2	-	-	FL130	-	1,0
	TF	ODILO	-	033	034,1	8,0	-	FL110	FL110	-	1,0
CAD 9W	(UIR FIR)										
	IF	CAD	-	-	-	-	-	FL130	FL130	280	1,0
	TF	SOTIP	-	033	034,0	5,2	-	-	FL130	-	1,0
	TF	ODILO	-	033	034,1	8,0	-	FL110	FL110	-	1,0
HOLDING											
LORNI	-	LORNI	-	-	-	-	-	-	-	-	-
MOLBA	-	MOLBA	-	-	-	-	-	-	-	-	-
ODILO	-	ODILO	-	-	-	-	-	-	-	-	-
XERAM	-	XERAM	-	-	-	-	-	-	-	-	-
OKRIX	-	OKRIX	-	-	-	-	-	-	-	-	-
CAD	-	CAD	-	-	-	-	-	-	-	-	-
DIBES	-	DIBES	-	-	-	-	-	-	-	-	-