

RNP RWY 22												
RMK	-	MAG VAR 2020 1°E						REF NAV AID :-				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	OKSOK	-	-	-	-	-	-	-	-	-	-
	IF	OKSOK	-	-	-	-	-	-	-	170	-	-
INA OKSOK	TF	OXUBA	-	042	043.2	14.9	-	-	4000	-	-	1.0
	TF	MAGIP	-	127	127.5	3.4	-	2500	-	-	-	1.0
INA OXUBA	IF	OXUBA	-	-	-	-	-	-	4000	170	-	-
	TF	MAGIP	-	127	127.5	3.4	-	2500	-	-	-	1.0
APCH	IF	MAGIP	-	-	-	-	-	2500	-	-	-	-
	TF	FQT22	-	217	217.6	3.3	-	2500	2500	-	-	1.0
	TF	RW22	Yes	217	217.5	6.4	-	-	-	-	-3.50 / 49.0	0.3
	TF	QT510	Yes	216	217.5	5.0	-	-	-	-	-	1.0
	DF	OKSOK	-	-	-	-	R	2500	-	170	-	1.0