

RNP RWY31													
RMK	-								MAG VAR 2020 0,1°E			REF NAV AID : CAN	
Leg sequence		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMN Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG		-	XASUD	-	-	-	-	-	-	-	-	-	-
		IF	XASUD	-	-	-	-	-	3000	FL80	-	-	-
INA XASUD		TF	ERKAV	-	264	264.5	8.5	-	-	-	-	-	1.0
		TF	RK406	-	216	216.1	7.0	-	3000	3000	-	-	1.0
INA ERKAV		IF	ERKAV	-	-	-	-	-	-	-	-	-	-
		TF	RK406	-	216	216.1	7.0	-	3000	3000	-	-	1.0
INA ATGAL		IF	ATGAL	-	-	-	-	-	-	-	-	-	-
		TF	RK406	-	036	035.9	6.0	-	3000	3000	-	-	1.0
INA RK406		IF	RK406	-	-	-	-	-	3000	3000	-	-	-
		IF	RK406	-	-	-	-	-	3000	3000	-	-	-
APCH		TF	FRK31	-	305	305.5	5.0	-	3000	3000	-	-	1.0
		TF	RW31	Yes	305	305.4	8.5	-	-	-	-	-3.00 / 50	0.3
		TF	RK410	Yes	305	305.3	3.0	-	-	-	-	-	1.0
		DF	ATGAL	-	-	-	-	-	-	-	-	-	1.0
		TF	XASUD	-	055	054.7	19.7	-	3000	FL80	-	-	1.0