

STRASBOURG ENTZHEIM
PRECODING INA RNAV (GNSS) RWY 05

INA RNAV MIRGU/IZPIQ/LUPEN RWY 05												
RMK	GNSS Only		MAG VAR 2020 02.5°W							REF NAV AID :		
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	IZPIQ	-	-	-	-	-	-	-	-	-	-
HLDG	-	BAKIX	-	-	-	-	-	-	-	-	-	-
INA MIRGU-BAKIX	IF	MIRGU	-	-	-	-	-	FL150	FL220	250	-	-
	TF	STM33	-	036	038.1	17.2	-	FL100	FL150	250	-	1.0
	TF	BAKIX	-	036	038.3	7.1	-	7000	FL120	220	-	1.0
	TF	LOPSU	-	086	088.7	9.5	-	5500	7900	200	-	1.0
INA LUPEN-BAKIX	IF	LUPEN	-	-	-	-	-	FL150	FL200	250	-	-
	TF	ST435	-	301	303.3	13.7	-	FL110	FL150	220	-	1.0
	TF	ST445	-	227	229.7	13.4	-	7000	FL100	220	-	1.0
	TF	BAKIX	-	227	229.5	7.3	-	7000	-	220	-	1.0
INA LUPEN-LOPSU	IF	LUPEN	-	-	-	-	-	FL150	FL200	250	-	-
	TF	ST435	-	301	303.3	13.7	-	FL110	FL150	220	-	1.0
	TF	ST445	-	227	229.7	13.4	-	7000	FL100	220	-	1.0
	TF	LOPSU	-	136	138.4	6.0	-	5500	7900	200	-	1.0
INA IZPIQ	IF	IZPIQ	-	-	-	-	-	FL120	FL180	250	-	-
	TF	ST801		086	88.4	7.0		FL120	FL150	220		1.0
	TF	LOPSU	-	086	88.6	17.0	-	5500	7900	200	-	1.0