

NIMES GARONS

PRECODING RNP RWY 18

RNP RWY 18												
RMK	-							MAG VAR 2020 1.7° E			REF NAVAID :-	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	NG	-	-	-	-	-	-	-	-	-	-
INA TW500	IF	TW500	-	-	-	-	-	4000	-	185	-	-
	TF	ITW18	-	085°	086.9°	5.0	-	3000	-	-	-	1.0
INA TW502	IF	TW502	-	-	-	-	-	-	-	170 ⁽¹⁾	-	-
	TF	ITW18	-	265°	267.1°	3.3	-	3000	-	-	-	1.0
INA NG	IF	NG	-	-	-	-	-	-	FL 070	220	-	-
	TF	TW512	-	265°	266.5°	4.9	-	-	-	-	-	1.0
	TF	TW500	-	355°	357.0°	8.0	-	4000	-	185	-	1.0
	TF	ITW18	-	085°	086.9°	5.0	-	3000	-	-	-	1.0
	IF	ITW18	-	-	-	-	-	3000	-	-	-	-
APCH	TF	FTW18	-	175°	177.0°	5.0	-	3000	3000	-	-	1.0
	TF	RW18	yes	175°	177.0°	8.3	-	-	-	-	-3.0° / 49	0.3
	TF	TW510	yes	175°	177.0°	5.4	-	-	-	185	-	1.0
	DF	TW511	-	-	-	-	R	-	-	190	-	1.0
	TF	TW500	-	001°	003.1	16.0	-	4000	-	185	-	1.0
	TF	ITW18	-	085°	086.9°	5.0	-	4000	-	185	-	1.0
	TF	NG	-	176°	177.9	8.0	-	-	4000	-	-	1.0

(1) Arrivée TW502 interdite aux CAT.D / TW502 arrival prohibited for CAT.D