

WALLIS HIHIFO
PRECODING RNP RWY 08

RNP RWY 08													
RMK	-								MAG VAR 2020 11.6°E			Ref NAVD :-	
Leg sequence		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG		-	IWW08	-	-	-	-	-	-	-	-	-	-
INA IWW08		IF	IWW08	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
INA WW512		IF	WW512	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
		TF	IWW08	-	168	180.0	5.0	-	2000	-	-	-	RNP APCH
INA WW510		IF	WW510	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
		TF	IWW08	-	348	360.0	5.0	-	2000	-	-	-	RNP APCH
APCH		IF	IWW08	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
		TF	FWW08	-	078	090.0	5.0	-	2000	2000	-	-	RNP APCH
		TF	RW08	YES	078	090.0	5.9	-	-	-	-	-3 / 15	RNP APCH
		CA	-	-	078	089.9	-	-	1600	1600	185 MAX	-	RNP APCH
		DF	WW514	-	-	-	-	L	2000	2000	185 MAX	-	RNP APCH
		TF	WW512	-	258	270.0	8.0	-	2000	2000	-	-	RNP APCH