

WALLIS HIHIFO

PRECODING RNP RWY 26

RNP RWY 26													
RMK	-								MAG VAR 2020 11.6°E			Ref NAV AID :-	
Leg sequence		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG		-	IWW26	-	-	-	-	-	-	-	-	-	-
INA IWW26		IF	IWW26	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
INA WW412		IF	WW412	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
		TF	IWW26	-	168	179.9	5.0	-	2000	-	-	-	RNP APCH
INA WW410		IF	WW410	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
		TF	IWW26	-	348	359.9	5.0	-	2000	-	-	-	RNP APCH
APCH		IF	IWW26	-	-	-	-	-	2000	-	210 MAX	-	RNP APCH
		TF	FWW26	-	258	269.9	5.0	-	2000	2000	-	-	RNP APCH
		TF	RW26	YES	258	269.9	5.9	-	-	-	-	-3 / 15	RNP APCH
		CA	-	-	258	269.9	-	-	1600	1600	185 MAX	-	RNP APCH
		DF	WW414	-	-	-	-	R	2000	2000	185 MAX	-	RNP APCH
		TF	WW412	-	078	089.9	8.0	-	2000	2000	-	-	RNP APCH