

RNP RWY 30												
RMK									MAG VAR 2020 12,2° E			Ref NAVD :
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG	-	IWL30	-	-	-	-	-	-	-	-	-	-
INA IWL30	IF	IWL30	-	-	-	-	-	1700	-	175	-	RNP APCH
INA WL700	IF	WL700	-	-	-	-	-	1700	-	175	-	RNP APCH
	TF	IWL30	-	033	044.9	3.5	-	1700	-	175	-	RNP APCH
	IF	ONULU	-	-	-	-	-	1700	-	180	-	RNP APCH
INA ONULU	TF	WL700	-	078	090.4	12.0	-	1700	-	175	-	RNP APCH
	TF	IWL30	-	033	044.9	3.5	-	1700	-	175	-	RNP APCH
	IF	IWL30	-	-	-	-	-	1700	-	175	-	RNP APCH
APCH	TF	FWL30	-	303	314.9	3.5	-	1700	1700	-	-	RNP APCH
	TF	RW30	Yes	303	314.9	4.0	-	-	-	-	-3.7° / 15.0	RNP APCH
	TF	WL710	Yes	303	314.9	2.0	-	-	-	-	-	RNP APCH
	DF	WL700	-				L			175	-	RNP APCH
	TF	IWL30	-	033	044.9	3.5	-		1700	175	-	RNP APCH