

RNP RWY 13												
RMK								MAG VAR 2020 12,5° E			Ref NAVAID :	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG	-	IWR13	-	-	-	-	-	-	-	-	-	-
INA WR600	IF	WR600	-	-	-	-	-	1700	-	175	-	RNP APCH
	TF	IWR13	-	036	048.9	3.5	-	1700	-	175	-	RNP APCH
INA MIDIN	IF	MIDIN	-	-	-	-	-	1700	-	180	-	RNP APCH
	TF	WR600	-	026	038.0	5.6	-	1700	-	175	-	RNP APCH
	TF	IWR13	-	036	048.9	3.5	-	1700	-	175	-	RNP APCH
INA IWR13	IF	IWR13	-	-	-	-	-	1700	-	175	-	RNP APCH
APCH	IF	IWR13	-	-	-	-	-	1700	-	175	-	RNP APCH
	TF	FWR13	-	126	138.9	3.5	-	1700	1700	-	-	RNP APCH
	TF	RW13	yes	126	138.9	4.1	-	-	-	-	-3,5° / 15.0	RNP APCH
	TF	WR610	yes	126	138.9	2.0	-	-	-	-	-	RNP APCH
	DF	WR600	-	-	-	-	R	-	-	175	-	RNP APCH
	TF	IWR13	-	036	048.9	3.5	-	1700	-	175	-	RNP APCH