

Identification Procedure		RNP RWY 31					Dec MAG 2015 11,8°E			vertical angle (°) / TCH (m)	Nav Spec
Leg sequence	P/T	ID	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM or min)	Turn	MM level (FL or AMSL ft)	MAX level (FL or AMSL ft)		
INA WU192	IF	WU192						4600			RNAV1/RNP APCH
	TF	WU194		024	035.6	5		3300		170 MAX	RNAV1/RNP APCH
	TF	IWU31		294	305.6	5	L	2000			RNAV1/RNP APCH
INA WU194	IF	WU194						3300		170 MAX	RNAV1/RNP APCH
	TF	IWU31		294	305.6	5		2000			RNAV1/RNP APCH
	IF	IWU31									RNAV1/RNP APCH
APCH	TF	IWU31		294	305.6	4.5		2000	2000		RNP APCH
	TF	FWU31		314	325.6	5.2				-3,5°/15	RNP APCH
	CA	RW31	Yes	314	325.6			1200	1200		RNP APCH
	DF	WU190					R	3300			RNP APCH
	TF	WU194		204	215.6	4	R	3300			RNP APCH
HLDG	HM	WU194	Yes	294	305.6	T 1 min	L	3300	6000	170 MAX	RNAV1